



S300 Integrated Retail Smart PINpad

- Contactless, Chip, Magstripe
- Large Color Touch Screen
- Visa & MasterCard® NFC
- PCI PTS 4.x, SRED

PAX's S300 is the latest integrated retail payment solution for multilane merchants who wish to offer high levels of transactional security combined with contactless, e-signature, magnetic stripe and Chip & PIN. With state of the art levels of security design, including PCI PTS 4.x and SRED, the S300 protects and encrypts all transaction information. Featuring a large color touch screen and loudspeaker, the S300 comes with a 32-bit ARM11 processor and massive amounts of memory.

Your Payment Partner of Choice



S300 Integrated Retail Smart PINpad

Features & Benefits



Stability and Reliability

- 400MHz 32-bit ARM11 processor
- Chip & PIN, Magstripe, Contactless
- Advanced DDR & SDRAM technology
- Sleek compact design

Exceptional Security

- PCI PTS 4.x approved, SRED
- Secure key embedded area
- Supports RSA, AES, 3DES
- Supports HASH function

Open & Flexible Operating System

- Secure platform
- Easy software application development
- User-friendly interface with powerful GUI
- Multi-tasking OS maintains application integrity
- Plug-and-Play to extend functionality on-site

Multimedia Performance

- Loudspeaker
- Large color touch screen display
- Supports images

Specifications

Processor

32-bit ARM11

Memory

192MB (128MB Flash, 64MB DDR)

Display

3.5 inch 240 x 320 pixels color TFT LCD
Touch screen

Keypad

10 numeric keys, 5 function keys
Back-lighting

Magnetic Card Reader

Track 1 / 2 / 3, bi-directional

Smart Card Reader

EMV L1 & L2

Contactless Card Reader

MasterCard Contactless & Visa payWave
AMEX Expresspay
Discover DPAS
JCB J/Speedy
Interac Flash
ISO14443 Type A/B
Mifare, Felica, NFC

Card Slots

3 SAMs

Audio

Speaker, 90dB

Communication Cable

Single multi-port connector which supports up to:
1 x RS232 + 1 x USB2.0 Device + 1 x Ethernet

Accessories (optional)

Multi-function cable

Security

DUKPT, Master/Session, 3DES
ANSI / ISO9564 format 0, 1, 3
PIN ciphered key algorithm
ANSI X9.9 / X9.19 MAC algorithm

Environmental

0°C to 50°C (32°F to 122°F) operating temperature
10% to 93% relative humidity, non-condensing
-20°C to 70°C (-4°F to 158°F) storage temperature

Voltage (optional)

External power supply
5VDC, 0.5A

Physical

Length: 167mm
Width: 81mm
Height: 50mm

Weight

290g

Accessories (optional)

Multi-function Cable

Certifications

PCI PTS 4.x, SRED
EMV Contact L1 & L2
EMV Contactless L1
Visa payWave
MasterCard Contactless
AMEX Expresspay
Discover D-PAS
JCB J/Speedy
Interac Flash
MasterCard TQM

www.pax.us

This document is provided to you for informational purposes only. All features and specifications are subject to change without notice. PAX are either trademarks or registered trademarks of PAX Technology Limited in China and/or other countries. payWave® is a registered trademark of Visa, Inc. Mastercard and the Mastercard brand mark are registered trademarks of Mastercard International Incorporated. Contactless is the trademark of Mastercard International Incorporated. All other trademarks or brand names are the properties of their respective holders. Copyright 2016, PAX Technology Limited, All Rights Reserved.

